SCHEDA TECNICA

KLIS IPCAM-5M-NOB

Telecamera di rete bullet motorizzata 5MP con IR e True WDR

CARATTERISTICHE PRINCIPALI

La KLIS IPCAM-5M-NOB è una telecamera bullet di rete da 5 Megapixel, progettata per garantire immagini nitide e affidabili in applicazioni di videosorveglianza professionale. Grazie al supporto di più flussi video e agli avanzati codec H.264/H.265, offre prestazioni elevate e flessibilità sia per gli utenti sia per i gestori di sistema. La funzione True WDR assicura una qualità dell'immagine ottimale anche in scenari con forti contrasti luminosi o variazioni di luce improvvise.

NDAA Compliant, ideale per installazioni governative e infrastrutture critiche

Qualità dell'immagine
- Risoluzione 5 Megapixel
- True WDR (120 dB) per una corretta gestione dei contrasti
- Funzione True Day & Night, con ICR per visione notturna
- IR LED con portata fino a 40 m

Ottica
- Obiettivo motorizzato varifocale 2.7–12 mm, regolabile da remoto

Codec e streaming
- Supporto H.265 / H.264 / MJPEG
- Triple Stream simultanei
- Prestazioni fino a 5MP @ 25 fps con H.265

Ingressi/uscite e memoria
- Ingresso/uscita allarme: 1/1
- Ingresso/uscita audio: 1/1
- Supporto Micro SD: SDHC / SDXC

Alimentazione e connettività
- Alimentazione PoE o 12V DC
- Compatibile Onvif
- Accesso tramite browser: Edge, Firefox, Chrome

Funzioni avanzate
- Privacy Masking
- Protezione cavi integrata

Struttura e installazione
- Custodia metallica resistente
- Certificazione IP66 per uso esterno
- Adattatore per montaggio su palo disponibile

EUKLIS SRL

Viale Leonardo da Vinci 43,
20090 Trezzano sul Naviglio (MI)
02 48409267
info@euklis.com

TECHNICAL SPECIFICATIONS

IMAGE		
Lens		Motorized Varifocal 2.7~12mm, F1.3
Image Sensor	Type	1/2.8" CMOS Sensor
	Pixels	2688(H)x1520(V)
Min. Illumination		Color : 0.14Lux@F1.6 / BW : 0Lux@F1.6(IR LED On)
Scanning Mode		Progressive Scan
Wide Dynamic Range		True WDR(120dB)
Day and Night Mode		True D/N(Auto, Day, Night)
Noise Reduction		3DNR
Digital Zoom		12x
Exposure Control		Auto
White Balance Control		Auto, Manual
Metering Mode		Average, BLC, HLC
Image Effect		Flip, Mirror
Flicker Free Mode		50Hz, 60Hz
Shutter Speed		Auto(1/100.000~1sec), Manual
IR Illuminator		
	Distance	Up to 40m
Motorized Lens Control		Smart Focus, Manual, Auto
VIDEO/AUDIO		
Compression		H.264/H.265(Baseline, Main, High Profile), MJPEG
Bitrate Control		CBR, VBR
Resolution		2592x1944, 2560x1920, 2048x1536, 1920x1440, 1600x1200, 1280x960, 800x300, 640x480, 480x360
Frame Rate		Max. 25/30fps
Streaming		Triple Stream
Audio Compression		G.711
Audio Streaming		2 Way
SYSTEM		
Video Contents Analysis		Tampering, Line-Cross, Field Intrusion, Human Detection, Face Detection
Motion Detection Area		4 Programmable Area
Privacy Mask Zone		8 Programmable Zone
FTP Uploading		MJPEG
Event Notification		E-mail, FTP
Login Authority		Administrator, Operator, Guest
Event Buffering	FTP	Pre : 30sec, Post : 30sec
	SD Record	Pre : 30sec, Post : 30sec
Manual Trigger		4 Programmable Trigger
Security		Multi User Authority, IP Filtering, HTTPS
Network Time Sync		NTP Server, Synchronized Computer, Manual
Software Reset		Restart, Reset, Factory Default
Hardware Factory Reset		Yes
Auto Recovery		Backup, Restore
Remote Upgrade		Web Browsing(Edge, Chrome, Safari, Firefox), SmartManager
SD Recording Mode		Event, Continuous
NETWORK		
Protocol		TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Client Software		Built-In Web, ONVIF Compatible 3rd Party VMS
Max. User Connection		10 Users
API Support		API, Onvif Compliance
EXTERNAL IN/OUT		
Audio		1 Input, 1 Output(Terminal Block)
Alarm		1 Input, 1 Output(Terminal Block)
Ethernet		RJ-45
u-SD Card		SDHC, SDXC
ETC		
Operating Humidity		0~90% RH(Non-Condensing)
Operating Temperature		-20~+50℃
Power Supply		PoE(IEEE802.3af Compliance)/12VDC
Power Consumption		200mA(9W)@PoE / 710mA(7.6W)@12VDC
Dimension		90,4(W)x84(H)x285(D)mm
Net Weight		Approx. 850g
Ingress Protection		IP66
Vandal Proof		IK10

All specifications subject to change without notice

EUKLIS

Euklis s.r.l.
Via Leonardo da Vinci 43- 20090 Trezzano s/N (MI) - Italy
Tel. (+39) 02.48.40.92.67 - www.euklis.it